## PRELIMINARY DRAINAGE REPORT First Submittal

For

# CHRISTIAN BROTHERS AUTOMOTIVE CORPORATION CBAC 11416 EAST DESERT COVE AVENUE SCOTTSDALE, ARIZONA

Plan #	
Case # 59-bR-2=15	
Q-S#	May, 2016
Accepted	
☐ Corrections	
16 5/20 Pro	ject No.: 2073
Reviewed By Date	

Prepared for:

CHRISTIAN BROTHERS AUTOMOTIVE CORPORATION 17725 KATY FREEWAY, SUITE 200 HOUSTON, TX 77094

Prepared by:

## Site Consultants, Inc.

**Engineers** • **Surveyors** • **Consultants** 113 South Rockford Drive • Tempe, AZ 85281 Tel (480) 894-2820 • Fax (480) 894-2847

#### **TABLE OF CONTENTS**

1.0	INTRODUCTION AND SCOPE OF WORK	1
1.1 1.3 1.4 1.5	SCOPE OF WORK AND LIMITATIONS	1
2.0	PHYSICAL SETTING	
2.1	EXISTING SITE TOPOGRAPHY	2
3.0	MANAGEMENT OF OFF-SITE STORMWATER RUNOF	2
3.1	OFF-SITE FLOWS:	2
4.0	MANAGEMENT OF ON-SITE STORMWATER RUNOFF	3
4.1 4.2 4.2.1 4.3	SPECIAL CONDITIONS	3
5.0	FLOOD ZONE INFORMATION	.4
6.0 7.0	ESTIMATED REMAINING UNDERGROUND STORAGE TANK LIVE	
8.0	REFERENCES CITED AND REVIEWED	

#### **ATTACHMENTS**

Attachment No. 1	Vicinity Map
Attachment No. 2	Approved Site Plan
Attachment No. 3	Topographic Map
Attachment No. 4	Final Drainage Report - Shea Garden Nursey
Attachment No. 5	NOAA Atlas 2014 – Rainfall Precipitation Data
Attachment No. 6	FIRM Map
Attachment No. 7	(1st Folder) Preliminary Grading, Drainage & Paving Plan.
Attachment No. 8	(2 <sup>nd</sup> Folder) Aerial Map
Attachment No. 9	(3 <sup>rd</sup> Folder) City Topographic Map



Erp 3-31-2019

Site Consultants, Inc.

**Engineers • Surveyors • Consultants** 113 South Rockford Drive • Tempe, AZ 85281 Tel (480) 894-2820 • Fax (480) 894-2847

Note: This page left intentionally blank for future use!

**Engineers** • **Surveyors** • **Consultants** 113 South Rockford Drive • Tempe, AZ 85281 Tel (480) 894-2820 • Fax (480) 894-2847

#### 1.0 INTRODUCTION AND SCOPE OF WORK

This report presents the results of a drainage study conducted by Site Consultants, Inc. (SCI) at the request of Christian Brothers Automotive Corporation (client) for a new Christian Brothers Automotive Center (CBAC) located at NEC Frank Lloyd Wright Boulevard and Desert Cove Avenue (site). The purpose of this report is to provide an analysis of the proposed site redevelopment's impact, if any, on the existing site developments off-site and on-site drainage patterns and existing on-site retention facilities

#### 1.1 Scope of Work and Limitations

This report is focused on providing practical design information, evaluation, and calculations for statistical flood events up to and including the 100-year frequency flood. The procedures used herein are derived from, and performed with, currently accepted engineering methodologies and practices. Additionally, the criterion for this evaluation is designed to conform to currently applicable ordinances, regulations and policies affected by the appropriate jurisdictional regulatory authorities for the site.

The analysis presented herein focuses on developing design estimates of stormwater runoff resulting from a statistical evaluation of storm events of particular duration and frequency up to and including a 100-year frequency event. A storm event exceeding the 100-year frequency event may cause or create the risk of greater flood impact than is addressed and presented herein. However, the scope of this assessment does not include, neither did the client request, evaluation of stormwater runoff resulting from storm events exceeding the 100-year frequency event. Site Consultants, Inc. assumes no responsibility for actual flood damage, increased risks of flood damage, or increased construction or development cost resulting from or related to any such events. Nor shall SCI be responsible for any changes in or additions to, regulatory requirements that may result from, or be related to, any such events or changes in hydrologic or hydraulic conditions within the watershed.

In performing the services contained herein, SCI has or will receive information prepared or compiled by others. SCI as engineering professionals, are not required to verify the information, but may rely on the information unless actual knowledge concerning the validity of the information is known or is obvious to the professional. Therefore, SCI is entitled to rely upon the accuracy and completeness of this information without independent evaluation or verification.

#### 1.2 Site Location

The 1.33 net acre site is located at NEC Frank Lloyd Wright Boulevard and Desert Cove Avenue (site). The site is located in the southwest quarter of Section 22 of Township 3 North, Range 5 East of the Gila and Salt River Base and Meridian, Maricopa County, Arizona. The site can also be identified by the physical address 11416 East Desert Cove Avenue, Scottsdale, Arizona. The site is bounded on the north and east by Equestrian Apartments, on the south by East Desert Cove Avenue and on the west by Frank Lloyd Wright Boulevard.

### See Attachment No. 1 for Vicinity Map.

#### 1.3 Existing Site Development Improvements

The site is currently development and being operated as a nursey. Shea Gardens Nursey site improvements include a building, shade canopy structures, paved asphalt parking lot and surface landscape retention basin.

Existing site development also includes three electric towers (2 - APS & 1 - SRP), cell tower equipment building.

#### 1.4 Proposed Site Development Description

The proposed development for this parcel consists of the demolition of the existing on-site nursey facility improvements. The existing electric towers and cell tower equipment building will remain.

Two new single story buildings (1 vehicle service & 1 administration) will be constructed along with associated pavement parking lot, trash enclosure, associated landscape areas and a pedestrian access connection to the City right-of-way and permanent on-site underground retention basin.

See Attachment No. 2 for "Site Plan".

#### 1.5 Regulatory Jurisdiction

The criterion used in the drainage design and analysis of the site was established using the guidelines as described in the following:

• Drainage Standards and Policies Manual for City of Scottsdale, dated, January 2010. (Reference 1).

#### 2.0 PHYSICAL SETTING

#### 2.1 Existing Site Topography

As noted in Section 1.3 the proposed site is currently being utilized as a nursey facility. The site generally slopes from the westerly property line (elevation 1469-feet) to southwest corner of site (elevation 1461-feet) with an approximate average slope of 2.4 percent.

The site has a landscape area along it's Frank Lloyd Wright Boulevard; based on the original drainage report prepared in conjunction with the 1993 nursey improvement plans, portions of the said landscape area was previously utilized as a retention basin, however, only a small depression in the basin area appears to remain.

See Attachment No. 3 for development area topographic map.

#### 3.0 MANAGEMENT OF OFF-SITE STORMWATER RUNOF

#### 3.1 Off-Site Flows:

The Equestrian Apartments located to the north and west of the proposed development has existing on-site stormwater retention facilities design for 100 year – 1 hour storm event based on Pre-Development versus Post Development conditions. Two offsite washes pass through the Equestrian Apartments one wash is pipe through the development the other is conveyed thorough the parking lot drive areas. The two flows from the wash converge at a point along the western property line of the Equestrian Apartments located north of the proposed CBAC development. The flows are conveyed to the southwest under Frank Lloyd Wright Boulevard via two (2) – 24-inch concrete

pipe. The pipes discharge into a survey wash at the southwest corner of Frank Lloyd Wright Boulevard and East Desert Cove Avenue.

The apartment complex has two primary drainage areas; the north drainage area outfalls into the said wash flow convergence location; the southern drainage area outfalls into East Desert Cove Avenue at the southwest corner of the apartment complex.

Offsite site flows from Frank Lloyd Wright Boulevard are conveyed south past the site via existing curb and gutter. Offsite site flows from East Desert Cove Avenue are conveyed west past the site via existing curb and gutter.

#### 4.0 MANAGEMENT OF ON-SITE STORMWATER RUNOFF

#### 4.1 Existing On-Site Hydrology – Redevelopment Area

According to the drainage report of the existing Shea Garden nursey prepared by Wiley & Associates, Inc. date November 1<sup>st</sup>, 1993; the existing site development was designed to retain 7,116 cf. of stormwater retention in a surface landscape basin. Said basin outfalls into Frank Lloyd Wright Boulevard at approximately 90-feet north of the East Desert Cove intersection. Although not specified in the drainage report the computed stormwater retention volume appears to be based on a 100-yr, 2-hr storm event. The retention required calculation used a weighted runoff coefficient of 0.52 and a rainfall intensity of 2.82.

#### See Attachment No. 4 for Final Drainage Report for Shea Gardens nursey.

### 4.2 Proposed On-Site Hydrology - Redevelopment Area

The proposed CBAC development will include the construction of permanent on-site stormwater retention facilities. Specifically said permanent on-site retention facilities will be sized to retain 100 percent of the 100 year – 2 hour storm event based on NOAA Atlas 2014 precipitation data. The storage facilities will be approximately 200 –If of 8-foot diameter underground pipe.

#### 4.2.1 Retention Calculations

The criteria used in the drainage design and analyses of the site were established using the guidelines as described in the following:

The required retention volumes were computed using the City of Scottsdale formula, Vr = C\*(P/12) \*A, to determine the required volume, where:

D = 2.30/12

C = 0.90

\*A = On-site Drainage Area (sf): Total = 57,936, sf

#### RETENTION VOLUME REQUIRED CALCULATIONS

DRAINAGE AREA (DA)	"C"	"P"	AREA (SF)	VOLUME REQUIRED (cf)
Net Site	0.9	2.30	57,936	9,994
TOTAL				9,994

See Attachment No. 5 for NOAA 2014 Rainfall Precipitation Data.

### **RETENTION VOLUME PROIVDED CALCULATIONS**

172 L.F. of 8-ft dia. Pipe =  $3.14 \times 16 \times 200 \text{ l.f.} = 10,014 \text{ cf.}$ 

**Total Retention Provided = 10,031** 

#### RETENTION VOLUME DISSIPATION CALCULATIONS

DRAINAGE AREA (DA)	RETENTION VOLUME (CF)	DRYWELL DISSIPATED RATE 0.1 CFS	CALCULATION Volume / Dissipation Rate	NUMBER WELLS REQUIRED	
Net Site Area	10,031	12,960 cf / 36 hrs / well	10,014 / 12,960	0.8 use 1	
TOTAL				1 wells	

#### 4.3 Special Conditions

No know special conditions at this time.

#### 5.0 FLOOD ZONE INFORMATION

The Maricopa County, Arizona and Incorporated Areas Flood Insurance Rate Map (FIRM) map number 04013C1780L, dated October 16, 2013, indicates that the site falls within Zone 'X'. Zone 'X' is defined by FEMA as:

Areas of 0.2% annual chance flood; areas of 1% annual chance flood with average depths of less than 1 foot or with drainage areas less than 1 square mile; and areas protected by levees from 1% annual chance flood.

See Attachment No. 6 for Firm Map.

#### 6.0 ESTIMATED REMAINING UNDERGROUND STORAGE TANK LIFE

TO BE DETERMINED

#### 7.0 SUMMARY AND CONCLUSIONS

1. Proposed site outfall elevation location into Frank Lloyd Wright Boulevard is in approximately the same location as the existing development.

- 2. Proposed site outfall elevation is 1463.00 feet.
- 3. Proposed finished floor Elevations are for structures are 1466.00 feet which is 2.6-feet above the proposed site outfall elevation.
- 4. Stormwater runoff from the proposed site development area will not be increased.
- **5.** Permanent proposed stormwater retention facilities exceed the existing on-site stormwater retention, therefore the stormwater runoff from the site development should decrease.

#### 8.0 REFERENCES CITED AND REVIEWED


- 1. City of Scottsdale Case Number 51-DR-85. Drainage Report / Grading Plans prepared for "The Equestrian Apartments", prepared by Drew-Nykorchuk, dated July 1<sup>st</sup>, 1985.
- 2. City of Scottsdale Case Number 127-DR-88#3. Hydrology Report for Shea Gardens Nursey, prepared by Wiley & Associates, Inc. dated November 1<sup>st</sup>, 1993.
- 3. Flood Insurance Rate Map (FIRM) Maricopa County, Arizona and Incorporated Areas, Map Number 04013C1480L, Federal Emergency Management Agency, November 16, 2013.
- 4. NOAA Atlas 14, Volume 1, Version 5 "Point Precipitation Frequency Estimates"


This document was prepared by the following:

Printed/Typed Name:

Michael J. Caylor, P.E.

Date: May, 2016







5450 e high street, auite 200 phoenix arizona 65054 p:4805155123 + 802513 7193 www.sra360.com

Automotive

11416 E. Desert Cove Ave. Scottsdale, Arizona 85259 Brothe

Christian


SITE PLAN

15-064


sheet title: SITE PLAN

sheet no.





CHRISTIAN BROTHERS AUTOMOTIVE CORPORATION



N89'48'12"W (BASIS OF BEARING)

UNDERGROUND UTILITIES & STORM DRAIN LOCATIONS SHOWN HERION ARE BASED ON FELD OBSERVATIONS AND AVAILABLE MAPS OBTAINED FROM UTILITY COMPANIES AND THE CITY OF PEORIA, AZ. ACTUAL LOCATIONS MAY VARY FROM LOCATIONS SHOWN HEREON.

THE NORTH LINE OF THE SOUTHWEST QUARTER OF SECTION 22, TOWNSHIP 3 NORTH, RANGE 5 EAST OF GILA AND SALT RIVER BASE AND MERIDIAN THE SAID LINE BEARS N8848124, AS SHOWN PER MAP OF DEDICATION FOR ADDBE RANCH RECORDED IN BOOK 298, PAGE 38, M.C.R.

THIRE ELETATION TABLE				
POINT #	WIRE ELEVATION			
₩ı	1531.0			
W2	1536.9			
₩3	1533.3			
₩4	1555.0			
₩5	1541.4			
₩5	1541.3			
W7	1542.8			
W8	1542.4			
- W9	1533.8			
WID	1535.2			
W11	1530.6			
W12	1537.3			
₩13	1522.2			
W14	1517.3			
<b>W</b> 15	1517.2			
W16	1519.0			
W17	1519.2			
агж	1544,5			
W19	1518.5			
₩20	1516.5			
₩21	1523.8			

1523.5

onsultants,

Sife

S AUTOMOTIVE CORPORATION SERT COVE AVENUE SURVEY CHRISTIAN E 11416



EXPIRES 6-30	- 2016
PROJECT NO.:	2073
SCALE: 1	<b>– 30</b> .
DRAWN BY:	нто
CHECKED BY:	GES

DWG: 2073-V-ALTA

OF

#### HYDROLOGY REPORT

FOR

SHEA GARDENS
IN THE S.W.1/4 OF SEC.22 T3N R5E
WILEY & ASSOCIATES JOB # 4430

PREPARED FOR: TIM TOLMAN 1134 E. MANCY LANE PHOEMIX, ARIZONA 85040

LEONARD GOSTINSKI

Andified 12-1-93

WILEY & ASSOCIATES, INC. SURVEYORS & ENGINEERS 3200 N. HAYDEN ROAD SUITE B-200 SCOTTSDALE, AZ. 85251

#### OFF-SITE DRAINAGE

This project is located at the Northeast Corner of Frank Lloyd Wright Boulevard and Desert Cove, runoff flows from East to West.

The East line of this project is bordered by the parking lot and retention basin for Scottsdale Equestrian Apartments, effectively eliminating all off site drainage.

Runoff for Desert Cove is directed West to Frank Lloyd Wright Boulevard which directs runoff to the South.

#### ON-SITE RUNOFF

On-site runoff for this project is directed West and South to a retention basin at the Southwest corner of the property (see sketch, page 2). See retention basin storage, page 5. Ultimate lot overflow shall be into Frank Lloyd Wright boulevard via retention basin overflow (see sketch, page 2, see rational calc.s page 3 & 4).

The Pinish Flood shall be free from inundation from a one hundred (100) year storm.

CONC UNE. SWA! WLEY & ASSOCIATES, INC. Surveyors — Engineers 3200 N. Heyden Reed \* 1>--POOR QUALITY Scottsdale, Arizona 85252 **ORIGINAL** FRANK EXIST ACH LLOYD WRIGHT BLVD. EXTRUDED CURB N.T.S. 30' ANGHT OF MAY BK 298, PG. 38

HYDROLOGIC DESIGN DATA SHEET RATIONAL METHOD

WILEY & ASSOCIATES INC. SURVEYORS AND ENGINEERS 3200 N. HAYDEN RD. #130 SCOTTSDALE, AZ. 85251

#### LOCATION DATA:

Project: SHEA GARDENS Location: SEC. 22, T.3 N.,R.5 E.

Project No.: 4430 Station: Name of Stream: PRE-DEV. Drng.Area: ON-SITE

#### DESIGN DATA:

Drainage Area: 1.33 acres Drainage Length: Top of Drainage Area Bottom of Drainage Area Drainage Area Slope: 280.00 feet 1470.00 feet 1462.00 feet 2.8571 % 2.31 minutes ( min. 5 minutes) 0.35 Time of Concentration (Tc) Runoff Coefficient (C)

#### DESIGN COMPUTATIONS:

Design Frequency	Precipitation Data	Rainfall !	Peak Discharge Q = CIA
(Yr)	6 Hr. 24 Hr. 1 Hr.		(cfs)
5	1.29	4.5	2
10	1.55	5.8	3
25	1.94	6.7	3
50	2.22	7.8	4
100	2.37	8.3	4
			ERR

REMARKS:

Computed By: B.G.

Date: 9-30-93

HYDROLOGIC DESIGN DATA SHEET RATIONAL METHOD

WILEY & ASSOCIATES INC. SURVEYORS AND ENGINEERS 3200 N. HAYDEN RD. #130 SCOTTSDALE, AZ. 85251

LCCATION DATA:

Project: SHEA GARDENS

Location: SEC. 22, T.3 N., R.5 E.

Project No.: 4430 Station:
Name of Stream: PRE-DEV. Drng.Area:ON-SITE

DESIGN DATA:

1.33 acres Drainage Area: Drainage Length: Top of Drainage Area Bottom of Drainage Area 280.00 feet 1470.00 feet 1462.00 feet Drainage Area Slope: 2.8571 % Time of Concentration (Tc)

2.31 minutes ( min. 5 minutes)

Runoff Coefficient (C) 0.52

#### DESIGN COMPUTATIONS:

Design Frequency	Precipitation Data	Rainfall :	Peak Discharge
(Yr)	6 Hr. 24 Hr. 1 Hr.		(cfs)
5	1.29	4.5	3
10	1.55	5.8	4
25	1.94	6.7	5
50	2.22	7.8	5
100	2.37	8.3	6
			ERR

REMARKS:

Computed By: B.G.

Date: 9-30-93

#### RETENTION CALLLCULATIONS

RETENTION VOLUME =  $\frac{D}{12}$  (Cd X Cu)

"C" FACTOR WEIGHTING

17856 S.F. OF PAVEMENT AND ROOF X .91 = 16249 39960 LANDSCAPING AND NURSERY AREA X .35 = 13986 30235 S.F.

> 30235 57816 = .52 WEIGHTED "C" FACTOR

D = 2.37"

A = 57816 SQ. FT.

Cd = .52

Cu = .35

V = 2.82 (57816) X .52 = 7065 OF RETENTION REQUIRED

RETENTION PROVIDED

NURSERY AREA = 2880 CF SOUTHWEST BASIN = 4236 CF

TOTAL RETENTION PROVIDED = 7116 CF



NOAA Atlas 14, Volume 1, Version 5 Location name: Scottsdale, Arizona, US\* Latitude: 33.5866°, Longitude: -111.8341° Elevation: 1471 ft\* \* source: Google Maps



#### POINT PRECIPITATION FREQUENCY ESTIMATES

Sanja Perica, Sarah Dietz, Sarah Heim, Lillian Hiner, Kazungu Maitaria, Deborah Martin, Sandra Pavlovic, Ishani Roy, Carl Trypaluk, Dale Unruh, Fenglin Yan, Michael Yekta, Tan Zhao, Geoffrey Bonnin, Daniel Brewer, Li-Chuan Chen, Tye Parzybok, John Yarchoan

NOAA, National Weather Service, Silver Spring, Maryland

PF tabular | PF graphical | Maps & aerials

#### PF tabular

PDS-based point precipitation frequency estimates with 90% confidence intervals (in inches) <sup>1</sup>										
Duration				Averag	ge recurrenc	e interval ()	/ears)			
	1	2	5	10	25	50	100	200	500	1000
5-min	<b>0.196</b> (0.163-0.243)	<b>0,257</b> (0.214-0.317)	<b>0.346</b> (0.286-0.427)	<b>0.416</b> (0.341-0.510)	<b>0.508</b> (0.410-0.621)	<b>0.579</b> (0.462-0.703)	<b>0.652</b> (0.511-0.790)	<b>0.725</b> (0.559-0.877)	<b>0,823</b> (0.619-0.996)	<b>0.898</b> (0.661-1.09)
10-min	<b>0.299</b> (0.247-0.369)	<b>0.390</b> (0.325-0.482)	<b>0.527</b> (0.435-0.649)	<b>0.632</b> (0.518-0.776)	<b>0.773</b> (0.625-0.945)	<b>0.882</b> (0.703-1.07)	<b>0.993</b> (0.778-1.20)	<b>1.10</b> (0.851-1.33)	<b>1.25</b> (0.942-1.52)	<b>1.37</b> (1.01-1.66)
15-min	<b>0.370</b> (0.307-0.457)	<b>0.483</b> (0.403-0.598)	<b>0.654</b> (0.539-0.805)	<b>0.784</b> (0.643-0.961)	<b>0.959</b> (0.774-1.17)	1.09 (0.872-1.33)	<b>1.23</b> (0.964-1.49)	<b>1.37</b> (1.05-1.65)	<b>1.55</b> (1.17-1.88)	<b>1.70</b> (1.25-2.05)
30-min	<b>0,498</b> (0.413-0.615)	<b>0.652</b> (0.543-0.805)	<b>0.880</b> (0.726-1.08)	<b>1.06</b> (0.865-1.29)	<b>1,29</b> (1.04-1.58)	<b>1,47</b> (1.17-1.79)	<b>1.66</b> (1.30-2.01)	<b>1.84</b> (1.42-2.23)	<b>2.09</b> (1.57-2.53)	<b>2.28</b> (1.68-2.77)
60-min	<b>0.617</b> (0.511-0.762)	<b>0.806</b> (0.672-0.996)	<b>1.09</b> (0.899-1.34)	<b>1.31</b> (1.07-1.60)	<b>1.60</b> (1.29-1.95)	<b>1.82</b> (1.45-2.21)	<b>2.05</b> (1.61-2.48)	<b>2.28</b> (1.76-2.76)	<b>2.59</b> (1.95-3.13)	<b>2.82</b> (2.08-3.42)
2-hr	<b>0.721</b> (0.605-0.868)	<b>0.933</b> (0.785-1.13)	<b>1.24</b> (1.04-1.50)	<b>1.48</b> (1.23-1.78)	<b>1.80</b> (1.48-2.15)	<b>2.04</b> (1.65-2.44)	<b>2.30</b> (1.83-2.74)	<b>2.55</b> (1.99-3.04)	<b>2.89</b> (2.21-3.44)	<b>3.15</b> (2.36-3.78)
3-hr	<b>0.788</b> (0.661-0.967)	<b>1.01</b> (0.850-1.24)	<b>1.32</b> (1.10-1.62)	<b>1.57</b> (1.30-1.91)	<b>1.91</b> (1.56-2.32)	<b>2.19</b> (1.76-2.64)	<b>2.47</b> (1.95-2.98)	<b>2.77</b> (2.15-3.33)	3.17 (2.39-3.81)	<b>3,50</b> (2.58-4.21)
6-hr	<b>0.947</b> (0.813-1.13)	<b>1.20</b> (1.03-1.42)	<b>1.53</b> (1.30-1.81)	<b>1.79</b> (1.51-2.11)	<b>2.15</b> (1.80-2.52)	<b>2.43</b> (2.00-2.84)	<b>2.72</b> (2.21-3.18)	<b>3.02</b> (2.40-3.54)	<b>3,42</b> (2.66-4.01)	<b>3.74</b> (2.84-4.39)
12-hr	<b>1,07</b> (0,925-1,25)	<b>1.35</b> (1.17-1.58)	<b>1.70</b> (1.47-1.98)	<b>1.98</b> (1.69-2.30)	<b>2,35</b> (1,99 <b>-</b> 2,73)	<b>2.64</b> (2.21-3.06)	<b>2.94</b> (2.42-3.40)	<b>3.24</b> (2,64-3.75)	3.64 (2.89-4.23)	<b>3.95</b> (3.08-4.62)
24-hr	<b>1.26</b> (1.12-1.44)	<b>1,60</b> (1.43-1.84)	<b>2.08</b> (1.84-2.37)	<b>2.45</b> (2.16-2.79)	<b>2,97</b> (2,60-3,38)	<b>3.38</b> (2.94-3.84)	<b>3.81</b> (3.28-4.33)	<b>4.25</b> (3.63-4.83)	<b>4.86</b> (4.09-5.53)	<b>5.35</b> (4.45-6.10)
2-day	<b>1.38</b> (1.22-1.58)	<b>1.77</b> (1.56-2.02)	<b>2.32</b> (2.05-2.65)	<b>2.76</b> (2.43-3.15)	3.38 (2.95-3.84)	3.87 (3.35-4.40)	<b>4.39</b> (3.77-5.00)	<b>4.93</b> (4.21-5.62)	<b>5.69</b> (4.78-6.50)	<b>6.30</b> (5.23-7.22)
3-day	<b>1.49</b> (1.32-1.69)	<b>1.91</b> (1.69-2.17)	<b>2.52</b> (2.22-2.86)	<b>3.01</b> (2.64-3.41)	3.70 (3.23-4.19)	<b>4.26</b> (3.69-4.82)	<b>4.85</b> (4.18-5.50)	<b>5.48</b> (4.68-6.22)	<b>6.37</b> (5.36-7.24)	<b>7.08</b> (5.90-8.08)
4-day	<b>1.59</b> (1.41-1.81)	<b>2.04</b> (1.81-2.32)	<b>2.71</b> (2.39-3.06)	<b>3.25</b> (2.86-3.67)	<b>4.02</b> (3.52-4.54)	<b>4.64</b> (4.04-5.24)	<b>5.31</b> (4.59-6.00)	<b>6.03</b> (5.15-6.82)	<b>7.04</b> (5.93-7.97)	<b>7.86</b> (6.56-8.94)
7-day	<b>1.79</b> (1.57-2.04)	<b>2.29</b> (2.02-2.61)	<b>3.05</b> (2.68-3.47)	<b>3.66</b> (3.20-4.16)	<b>4.53</b> (3.94-5.14)	<b>5.24</b> (4.53-5.94)	<b>6.00</b> (5.14-6.80)	<b>6.80</b> (5.79-7.74)	<b>7.95</b> (6.67-9.05)	<b>8.89</b> (7.37-10.2)
10-day	<b>1.95</b> (1.73-2.22)	<b>2.51</b> (2.22-2.85)	<b>3.33</b> (2.93-3.77)	<b>3.99</b> (3.50-4.51)	<b>4.92</b> (4.29-5.56)	<b>5.67</b> (4.92-6.40)	<b>6.48</b> (5.58-7.32)	<b>7.33</b> (6.26-8.29)	<b>8.53</b> (7.19-9.66)	<b>9.50</b> (7.92-10.8)
20-day	<b>2.42</b> (2.14-2.74)	<b>3.12</b> (2.76-3.53)	<b>4.13</b> (3.65-4.67)	<b>4.90</b> (4.31-5.53)	<b>5.94</b> (5.21 <b>-</b> 6.71)	<b>6.75</b> (5.89-7.62)	<b>7.58</b> (6.58-8.57)	<b>8.42</b> (7.27-9.54)	<b>9.57</b> (8.19-10.9)	<b>10.5</b> (8.87-11.9)
30-day	<b>2.84</b> (2.51-3.21)	<b>3.66</b> (3.25-4.14)	<b>4.85</b> (4.28-5.46)	<b>5.75</b> (5.07-6.46)	<b>6.97</b> (6.12-7.84)	<b>7.91</b> (6.91-8.89)	<b>8.88</b> (7.72-9.98)	<b>9.88</b> (8.53-11.1)	<b>11.2</b> (9.61-12.7)	<b>12.3</b> (10.4-13.9)
45-day	<b>3.35</b> (2.97-3.78)	<b>4.32</b> (3.84-4.88)	<b>5.72</b> (5.07-6.45)	<b>6.76</b> (5.97-7.62)	<b>8.15</b> (7.17-9.19)	<b>9.21</b> (8.06-10.4)	<b>10,3</b> (8,96-11,6)	<b>11.4</b> (9.85-12.9)	<b>12.8</b> (11.0-14.6)	<b>14.0</b> (11.9-15.9)
60-day	<b>3.74</b> (3.33-4.21)	<b>4.85</b> (4.31-5.46)	<b>6.40</b> (5.68-7.20)	<b>7.54</b> (6.67-8.48)	<b>9.03</b> (7.96-10.2)	<b>10.2</b> (8.91-11.4)	<b>11.3</b> (9.86-12.7)	<b>12.4</b> (10.8-14.0)	<b>13.9</b> (12.0-15.7)	<b>15.0</b> (12.9-17.1)

<sup>&</sup>lt;sup>1</sup> Precipitation frequency (PF) estimates in this table are based on frequency analysis of partial duration series (PDS).


Numbers in parenthesis are PF estimates at lower and upper bounds of the 90% confidence interval. The probability that precipitation frequency estimates (for a given duration and average recurrence interval) will be greater than the upper bound (or less than the lower bound) is 5%. Estimates at upper bounds are not checked against probable maximum precipitation (PMP) estimates and may be higher than currently valid PMP values.

Please refer to NOAA Atlas 14 document for more information.

Back to Top

#### PF graphical

PDS-based depth-duration-frequency (DDF) curves Latitude: 33.5866°, Longitude: -111.8341°



NOAA Atlas 14, Volume 1, Version 5

Created (GMT): Mon Nov 9 19:17:37 2015

#### Back to Top

#### Maps & aerials




Average recurrence interval (years)

#### Precipitation Frequency Data Server









#### Precipitation Frequency Data Server



#### Back to Top

US Department of Commerce
National Oceanic and Atmospheric Administration
National Weather Service
Office of Hydrologic Development
1325 East West Highway
Silver Spring, MD 20910
Questions?: HDSC,Questions@noaa.gov

Disclaimer

